

Built for tough jobs and long days.

Discharging grass out the rear of the mower leaves a clean cut. The FDR25 distributes grass evenly over a wide surface, and it doesn't discharge into unwanted areas.



Solid rubber tires on 72" model are sandwiched between the rim halves and bolted in.



Main drive cast iron pulley offers superior strength and belt slippage control.

Some tractor and tire combinations do not allow enough room for mower hook-up. Longer lower hitch clevises are available to easily correct this situation.



Blade spindles and bearings are precision fit in a cast iron housing.



	FDR2572	FDR2584
Horsepower	15-50 HP	
Hitch	Cat. 1	
Working Width (cm)	72" (183)	84" (213)
Overall Width (cm)	74-7/8" (190)	86-1/2" (220)
Weight - lb (kg)	718 (326)	812 (368)
Mowing Height	3/4" - 5-1/4"	
Discharge	Rear	
Lower Hitch	Floating Clevis w/Plated Pins	
Top Link	Floating Clevis	
Deck Material Thickness	3/16"	
Blades 3 ea. Heat Treated Alloy Steel	1/4" x 2-1/2" x 25"	5/16" x 2-1/2" x 29"
Blade Overlap	1-1/4"	
Blade Spindles	Greaseable	
Deck Spindle Housings	Cast Iron Greaseable Hubs	
Blade Tip Speed	18,130 fpm	17,210 fpm
Caster Gauge Wheels, 4-each	3-1/4" x 10" Solid Rubber Tire	4" x 11" Semi-solid
Caster Wheel Spindle	1" Diameter Stressproof® Material	
Drive Train	540 RPM B-Section V-Belt	
Driveline	Heavy-duty w/Quick Coupler	
Front Roller	Optional	

*See dealer for complete warranty information.

Color Options:  



- Lower hitch clevises adjust in and out for greater leverage
- Floating 3-point for superior ground hugging capabilities
- 1" Stressproof® wheel spindles with nylon bushings for smooth casting
- Single B-section Kevlar® belt, spring-loaded for maximum performance
- Rounded front corner without lip helps protect trees and fences
- Grease bearings from top without removing belt covers